




HSF



REV.	DESCRIPTION	DATE	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	02/18/13'	Bruce		Roc.W

- NOTES:
1. MATERIAL SEE TABLE 1;
 - 2.ELECTRICAL PERFORMANCES;
2-1.RATED CURRENT:5A;
2-2.RATED VOLTAGE:250V AC/DC;
2-3.CONTACT RESISTANCE: 25 mΩ Max;
2-4.INSULATION RESISTANCE: 5000MΩ min. Measured at 500V DC;
2-5.WITHSTANDING VOLTAGE: 1000V AC for 1 Min.;
 3. MECHANICAL PERFORMANCES:
3-1.DURABILITY:500 CYCLES FOR PLATING GOLD 30u";
3-2.OPERATION TEMPERATURE:-40° To +105°C;

TABLE 1

ITEM	COMPONENT	Q'TY	MATERIAL	COLOR/FINISH
1	HOUSING	1	PBT	SEE TABLE 2
2	TERMINAL	N	BRASS	SEE TABLE 3
3	FORET SHELL	1	STEEL	NI OVER ALL
4	BACK SHELL	1	STEEL	TIN OVER NI

TABLE 2

PART NO.	HOUSING COLOR
YWSDB-P15B00**	BLACK
YWSDB-P15U00**	BLUE
YWSDB-P15W00**	WHITE

TABLE 3

SELECTIVE GOLD TYPE			GOLD OVER ALL		
CODE:**	CONTACT AREA	OTHER AREA	CODE:**	CONTACT AREA	OTHER AREA
S1	GOLD FLASH	TIN	A1	GOLD FLASH	GOLD FLASH
S2	GOLD 3u"	TIN	A2	GOLD 3u"	GOLD FLASH
S3	GOLD 10u"	TIN	A3	GOLD 10u"	GOLD FLASH
S4	GOLD 15u"	TIN	A4	GOLD 15u"	GOLD FLASH
S5	GOLD 30u"	TIN	A5	GOLD 30u"	GOLD FLASH

TOLERANCES UNLESS OTHERWISE SPECIFIED GENERAL X ±-- X ±0.40 XX ±0.25 XXX ±-- ANGLES ±3°	DRAWN Bruce 02/18/13'		TITLE 2.77 PITCH,D_SUB,15 CIRCUIT PLUG, STAMP TERMINAL,SOLDER TYPE, WITHOUT SCREW	
	DESIGN Bruce 02/18/13'			
	CHECKED 			
	APPROVED Roc.W 02/18/13'			
SCALE 1:1	3D FILE YWSDB-P1500	SERIES YWSDB		SIZE A4
SHEET 1 OF 1		DWG NO. C_YWSDB-P1500		REV. A
UNIT mm				

This document and information contained herein are the property of YW Precision Electronics(Guangdong)Co.Ltd
copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture
or sale of apparatus without permission

All materials meet the YW Precision Electronics(Guangdong)Co.Ltd spec.
environment-related substances management technical standard