




HSF

REV.	DESCRIPTION	DATE	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	02/18/13'	Bruce		Roc.W



NOTES:

1. MATERIAL SEE TABLE 1;
2. ELECTRICAL PERFORMANCES:
 - 2-1. RATED CURRENT: 5A;
 - 2-2. RATED VOLTAGE: 250V AC/DC;
 - 2-3. CONTACT RESISTANCE: 25 mΩ Max;
 - 2-4. INSULATION RESISTANCE: 5000MΩ min. Measured at 500V DC;
 - 2-5. WITHSTANDING VOLTAGE: 1000V AC for 1 Min.;
3. MECHANICAL PERFORMANCES:
 - 3-1. DURABILITY: 500 CYCLES FOR PLATING GOLD 30u";
 - 3-2. OPERATION TEMPERATURE: -40° To +105°C;

TABLE 1

ITEM	COMPONENT	Q'TY	MATERIAL	COLOR/FINISH
1	HOUSING	1	PBT	SEE TABLE 2
2	TERMINAL	N	BRASS	SEE TABLE 3
3	FORET SHELL	1	STEEL	NI OVER ALL
4	BACK SHELL	1	STEEL	TIN OVER NI

TABLE 2

PART NO.	HOUSING COLOR
YWSDB-P25B00**	BLACK
YWSDB-P25U00**	BLUE
YWSDB-P25W00**	WHITE

TABLE 3

SELECTIVE GOLD TYPE			GOLD OVER ALL		
CODE:**	CONTACT AREA	OTHER AREA	CODE:**	CONTACT AREA	OTHER AREA
S1	GOLD FLASH	TIN	A1	GOLD FLASH	GOLD FLASH
S2	GOLD 3u"	TIN	A2	GOLD 3u"	GOLD FLASH
S3	GOLD 10u"	TIN	A3	GOLD 10u"	GOLD FLASH
S4	GOLD 15u"	TIN	A4	GOLD 15u"	GOLD FLASH
S5	GOLD 30u"	TIN	A5	GOLD 30u"	GOLD FLASH

TOLERANCES UNLESS OTHERWISE SPECIFIED		
GENERAL	X	±--
	.X	±0.40
	.XX	±0.25
	.XXX	±--
ANGLES		±3°
SCALE	1:1	
SHEET	1 OF 1	
UNIT	mm	
		

DRAWN	DATE
Bruce	02/18/13'
DESIGN	DATE
Bruce	02/18/13'
CHECKED	DATE
	
APPROVED	DATE
Roc.W	02/18/13'
3D FILE	YWSDB-P2500

YW
connectivity

TITLE
2.77 PITCH, D_SUB, 25 CIRCUIT PLUG,
STAMP TERMINAL, SOLDER TYPE,
WITHOUT SCREW

SERIES	YWSDB	SIZE	A4
DWG NO.	C_YWSDB-P2500	REV.	A

This document and information contained herein are the property of YW Precision Electronics(Guangdong)Co.Ltd. copies are issued in strict confidence and shall not be reproduced or copied, or used as the basis of manufacture or sale of apparatus without permission.

All materials meet the YW Precision Electronics(Guangdong)Co.Ltd spec. environment-related substances management technical standard