

HSF

REV.	DESCRIPTION	DATE	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	02/18/13'	Bruce		Roc.W

NOTES:

1. MATERIAL SEE TABLE 1;
- 2.ELECTRICAL PERFORMANCES;
 - 2-1.RATED CURRENT:5A;
 - 2-2.RATED VOLTAGE:250V AC/DC;
 - 2-3.CONTACT RESISTANCE: 25 mΩ Max;
 - 2-4.INSULATION RESISTANCE: 5000MΩ min. Measured at 500V DC;
 - 2-5.WITHSTANDING VOLTAGE: 1000V AC for 1 Min.;
3. MECHANICAL PERFORMANCES:
 - 3-1.OPERATION TEMPERATURE: -40° To +105°C;
- 4.USE WITH TERMIANL:YWSDC-TP**

TABLE 1

ITEM	COMPONENT	Q'TY	MATERIAL	COLOR/FINISH
1	HOUSING 1	1	PBT	SEE TABLE 2
2	HOUSING 2	1	PBT	SEE TABLE 2
3	FORET SHELL	1	STEEL	Ni OVER ALL
4	BACK SHELL	1	STEEL	TIN OVER NI

TABLE 2

PART NO.	HOUSING COLOR
YWSDC-P37B0000	BLACK
YWSDC-P37U0000	BLUE
YWSDC-P37W0000	WHITE

YW
connectivity

TOLERANCES UNLESS OTHERWISE SPECIFIED		DRAWN	DATE	 connectivity			
GENERAL	X	Bruce	02/18/13'				
	.X	DESIGN	DATE				
	.XX	Bruce	02/18/13'				
ANGLES	.XXX	CHECKED	DATE	TITLE 2.77 PITCH,D_SUB,37 CIRCUIT PLUG, STAMP TERMINAL,CRIMPING TYPE, WITHOUT SCREW			
	±3°						
SCALE	1:1	APPROVED	DATE			SERIES	SIZE
SHEET	1 OF 1	Roc.W	02/18/13'				
UNIT	mm	3D FILE		DWG NO.	REV.		
		YWSDC-P3700		C_YWSDC-P3700	A		

