

HSF

REV.	DESCRIPTION	DATE	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	02/18/13'	Bruce		Roc.W




- NOTES:
- 1. MATERIAL SEE TABLE 1;
 - 2.ELECTRICAL PERFORMANCES;
 - 2-1.RATED CURRENT:5A;
 - 2-2.RATED VOLTAGE:250V AC/DC;
 - 2-3.CONTACT RESISTANCE: 25 mΩ Max;
 - 2-4.INSULATION RESISTANCE: 5000MΩ min. Measured at 500V DC;
 - 2-5.WITHSTANDING VOLTAGE: 1000V AC for 1 Min.;
 - 3. MECHANICAL PERFORMANCES;
 - 3-1.OPERATION TEMPERATURE:-40° To +105°C;
 - 4.USE WITH TERMIANL:YWSDC-TS**

TABLE 1

ITEM	COMPONENT	Q'TY	MATERIAL	COLOR/FINISH
1	HOUSING 1	1	PBT	SEE TABLE 2
2	HOUSING 2	1	PBT	SEE TABLE 2
3	FORET SHELL	1	STEEL	Ni OVER ALL
4	BACK SHELL	1	STEEL	TIN OVER NI

TABLE 2

PART NO.	HOUSING COLOR
YWSDC-S25B0000	BLACK
YWSDC-S25U0000	BLUE
YWSDC-S25W0000	WHITE



TOLERANCES UNLESS OTHERWISE SPECIFIED GENERAL X ±-- X ±0.40 XX ±0.25 XXX ±-- ANGLES ±3° SCALE 1:1 SHEET 1 OF 1 UNIT mm	DRAWN Bruce	DATE 02/18/13'		
	DESIGN Bruce	DATE 02/18/13'		
	CHECKED 	DATE 	TITLE 2.77 PITCH,D_SUB,25 CIRCUIT SOCKET, STAMP TERMINAL,CRIMPING TYPE, WITHOUT SCREW	
	APPROVED Roc.W	DATE 02/18/13'		
3D FILE YWSDC-S2500			SERIES YWSDC	SIZE A4
			DWG NO. C_YWSDC-S2500	REV. A

This document and information contained herein are the property of YW Precision Electronics(Guangdong)Co.Ltd
copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture
or sale of apparatus without permission

All materials meet the YW Precision Electronics(Guangdong)Co.Ltd spec.
environment-related substances management technical standard